

Sandblast Slags
Foundry Sands
Empire Blast Equipment
Bullard Safety Equipment
Sandblast Hose & Nozzles
Walnut Shells & Corn Cob Grit
Waterjet & Sandblast Garnet
Schmidt Blast Equipment
Silica Free Abrasives
Steel Shot & Grit
Aluminum Oxide
Glass Beads

## BLACK SHOT II #20 CRUSHED SLAG TECHNICAL DATA SHEET

Black Shot II crushed slag is a blend of water quenched coal slag, produced as a by-product of coal-fired generating stations and air cooled and crushed copper slag, produced as a by-product of copper smelters. This extremely inert iron silicate blend is angular, with an optimal bulk density and makes for an excellent sandblast abrasive with superior cleaning & cutting capabilities.

TYPICAL CHEMICAL ANALYSIS			TYPICAL SCREEN A	TYPICAL SCREEN ANALYSIS	
			% Retained on U.S. Star	% Retained on U.S. Standard Sieve	
Fe₂O3	Iron Oxide	49.02%	12 Mesh	0.42	
$SiO_2$	Silicon Dioxide	37.36%	20 Mesh	40.04	
CaO	Calcium Oxide	2.80%	30 Mesh	28.73	
$Al_2O_3$	Aluminum Oxide	7.79%	40 Mesh	17.61	
MgO	Magnesium Oxide	1.38%	50 Mesh	7.43	
Na₂O	Sodium Oxide	0.12%	70 Mesh	3.26	
$TiO_2$	Titanium Oxide	0.19%	100 Mesh	1.48	
K20	Potassium Oxide	0.33%	140 Mesh	0.62	
Zn	Zinc	<.80%	200 Mesh	0.26	
$SiO_2$	Crystalline Silica	<0.10%	270 Mesh	0.11	
LOI	Loss on Ignition	<0.10%	PAN	0.06	

Colour: Black

Grain Shape: Angular MOH Hardness: 7.0

Bulk Density: 126 lbs/cu.ft. (approx.)

**WARNING:** This product contains free silica. Repeated inhalation of respirable free silica may cause delayed lung injury known as silicosis. Follow current OSHA Safety and Health Standards for Crystalline Silica (Quartz). All products are sold without warranty expressed or implied and seller specifically does not warrant that these products are suitable for a particular purpose or purposes or are merchantable. Buyer agrees it does not rely on seller's skill or judgment to select or furnish these products. Buyer shall make its own tests to determine the suitability of such product for its purposes. **08/21** 

Tel: (905) 527-6000

Toll Free Tel: 1-888-794-5665 Fax: (905) 527-6660

Toll Free Fax: 1-888-794-7263 info@allredi-ca.com